

## AFYS215AVN2



## Features

- 21.5" TFT LCD 1920\*1080 Resolution
- 1000cd/m2 brightness ,with auto dimming function
- PCAP touch screen ,USB interface ,AG treatment
- Support VGA+DVI+HDMI signal input
- Support DC 12V 3A Power input
- Support Win XP, Win 7/8/10, win CE, Android, Linux OS
- IP65 Front water proof
- Support VESA and panel Mount mounting method



## Specifications

<b>Part Number</b>	AFYS215AVN2
<b>LCD size</b>	21.5"
<b>Resolution</b>	1920*1080
<b>Display Area</b>	476.64*268.11MM
<b>Brightness</b>	1000cd/m2 ,with auto dimming function
<b>Contrast Ratio</b>	1000:1
<b>Response Time</b>	:≤25ms
<b>View Angle</b>	89/89/89/89 (Typ.)(CR≥10)
<b>Touch Screen</b>	Projected Capacitive Touch screen, 4mm thickness cover glass
<b>Touch Accuracy</b>	<2.5mm
<b>Touch Transmittance</b>	>85%
<b>Touch input</b>	Finger, capacitive touch pen
<b>Interface</b>	VGA+USB touch +DVI+HDMI
<b>Power supply</b>	12V 4A.
<b>OS</b>	Win xp,Win7,Win8,Win CE, Android, Linux , Mac
<b>Working Environment</b>	-20 to 70 Degree Celsius (Operation) Relative Humidity 10%~90% (Non-condensing)
<b>Storage Temperature</b>	-30 to 80 Degree Celsius (Storage)
<b>Case Mounting</b>	Panel Mount, VESA
<b>Warrantee</b>	1 year



## Drawing :

